



Armour Dome Color Weatherproof CCD Cameras



- IP65 Weather Proof, Vandal Resistant housing made of Aluminium and Polycarbonate
- Housing: Beige Color
- Dome Cover: Transparent (type A)
Smoked (type B)
- Dimension: Ø140 X 115(H)mm, 1080g
- With 3D Mechanism (3 Axis)

600TVL

DD800 WDR 3.5 ~ 8mm / 600 Tv Lines / 0.00019 Lux



- 1/3" SONY Super HAD interlaced CCD, Day & Night with S/N Ratio 52dB
- Built-in DC Auto iris varifocal IR Corrected lens $f = 3.5 \sim 8\text{mm} / F1.4$
- **WDR** (Wide Dynamic Range) • **OSD** controlled by **RS-485** (PELCO D - 9600bps)
- High resolution of **600 TV lines** • 0.03 Lux (color mode) / **0.00019 Lux** (B/W mode)
- Power 12VDC - 120mA • Privacy masking, Motion detection, Mirror Function
- Super DNR, Digital Noise Reduction technology save 70% of DVR Storages
- For excellent sensitivity using **Sens-UP function (2X~256X)**
- HLC (high Light Compensation) • BLC (Intelligent selectable BLC function)
- Digital ZOOM X4

580TVL

DD 906 2.9 ~ 10mm / 580 Tv Lines / 0.0006 Lux



- 1/3" SONY Super HAD interlaced CCD, Day & Night with S/N Ratio 52dB
- Built-in DC Auto iris varifocal IR Corrected lens $f = 2.9 \sim 10\text{mm} / F1.2$
- High resolution of **580 TV lines** • 0.15Lux (color mode) / **0.0006 Lux** (B/W mode)
- Power 12VDC - 150mA • **OSD Menu**, Privacy masking, Motion detection, Mirror Function
- Super DNR, super noise reduction technology save 70% of DVR Storages
- For excellent sensitivity using **Sens-UP function (2X~256X)** • DIS (Digital Image Stabilizer)
- HLC (high Light Compensation) • BLC (Intelligent selectable BLC function)

560TVL

DD 705 3.5 ~ 8mm / 560 Tv Lines / 0.3 Lux



- 1/3" SONY Super HAD interlaced CCD, Day & Night with S/N Ratio 50dB (AGC-off)
- Built-in DC Auto iris varifocal lens $f = 3.5 \sim 8\text{mm} / F1.4$
- High resolution of **560 TV lines** • **0.2 Lux (color mode)**
- Power 12VDC - 100mA • **OSD Menu**, Privacy masking, Motion detection, Mirror Function
- BLC (Intelligent selectable BLC function programmable in 64 zones)
- Video Adjustment: Brightness, Contrast, Saturation and Hue, Color BLUE, Color RED..
- Programming Gamma: Custom/ 0.05~1.0 • Adjustable Shutter speed
- Shutter Speed: Auto / FLK / Manual 1/50 ~ 1/1000.000sec for PAL system
- Day & Night Function: AUTO / COLOR/ Black & White (adjustable level and delay)